

Technical specifications Coronis 5MP Mammo display

Display	MDMG-5121
Display technology	TFT AMLCD Dual Domain IPS Grayscale
Active screen diagonal	540.9 mm (21.3")
Active screen width	377.9 mm (13.3")
Active screen height	422.4 mm (16.6")
Pixel pitch	0.165 mm (0.0065")
Native resolution	2048 x 2560 pixels
Dark room contrast	900:1 max
Maximum luminance	1000 cd/m ² (342 fL) max
DICOM calibrated luminance	Factory Default 600 cd/m ² , Maximum Calibrated 850 cd/m ² (248 fL)
Luminance uniformity	90% typical with PPU
Viewing angle (hor./vert.)	176° (at 10:1 contrast)
Stabilization, calibration and automated QA	Embedded I-Guard
Digital video input	DVI
Display control and communication	DDC (complying to DDC2Bi)
Digital video / DDC input connector	One physical DVI connector, one cable
USB	USB-hub with 1 up- and 2 downstream ports, 1 endpoint
Supported resolutions	2048 x 2560
Display dimensions portrait (WxHxD)	408 x 592 x 217 mm (16.1 x 23.3 x 8.5")
Display weight	13.5 kg (29.7 lb)
Ergonomics	Tilt & swivel base, 100 mm VESA mounting standard, AR coated front cover
Display controls	Display on/off, backlight adjustments, OSD
Safety approvals	CE, CCC, KETI, UL60601-1-2
Emission approvals	EN 55022 LIMIT B, FCC class B, EN 61000-3-2
Operational temperature range	0°C to +35°C (32°F to 95°F)
Within spec temperature range	+15°C to +30°C (59°F to 86°F)
Power requirements (extern. power supply)	0 to 264 VAC, 45 to 65Hz
Power consumption	85 W max
Power save	Supports DVI-DMPM (when DVI input selected)

Technical specifications display controller

Display controller	BarcoMed 5MP2FH	MXRT
Bus	PCIe	PCIe
Bus clock speed	2.5 GHz	2.5 or 5.0 GHz
Bus width	4 bit	16 bit
Power consumption	< 15 W	< 76 Watt
Form factor	167.6 x 106.7 (6.6" x 4.2")	249 x 111 mm (9.8 x 4.38")
Operating system	Microsoft Windows® XP, Vista	Microsoft Windows® XP, Vista
Display configuration	Dual-head portrait or landscape	Dual-head portrait or landscape
Graphics accelerator	Barco AURA technology	ATI GPU
Pixel clock rate	340 MHz	340 MHz
Display memory	512 MB	1024 MB
VGA	VGA controller	VGA controller
Electrical standard	Dual DVI complying to VESA A DVI Rev. 1.0 spec	Dual DVI complying to VESA A DVI Rev. 1.0 spec
Video output connectors	2x DVI connectors (one/head)	2x DVI connectors (one/head)
Supported resolutions & refresh rates	2048 x 2560 @ 50Hz	2048 x 2560 @ 50Hz
EMI approvals and compliance	CE, FCC Class B, EN55022 B, EN 50082-1	CE, FCC Class B, EN55022 B, EN 50082-1
Operational temperature	0°C to +60°C (32°F to 140°F) Storage: -40°C to +85°C (-40° to 185°F)	0°C to +60°C (32°F to 140°F) Storage: -40°C to +85°C (-40° to 185°F)

The Coronis 5MP Mammo display system includes:

- Two 5 MegaPixel grayscale flat panel displays
- BarcoMed 5MP2FH or MXRT display controller
- MediCal QAWeb software for intervention-free QA
- Display driver
- Digital cabling

Request more information

Europe, Middle East,
Africa & Latin America
Phone: +32 56 233 557
sales.medical.eu@barco.com

North America
Phone: +1 866 302 7939
sales.medical.us@barco.com

Taiwan
Phone: +886 2 8221 6868
sales.medical.apac@barco.com

South Korea
Phone: +82 2 2175 8900
sales.medical.apac@barco.com

China
Phone: +86 21 6091 2222
sales.medical.apac@barco.com

Singapore
Phone: +65-6243.7610
sales.medical.apac@barco.com

India
Phone: +91 120 4020000
sales.medical.apac@barco.com

Australia
Phone: +61 3 9646 5833
sales.medical.apac@barco.com

Japan
Phone: +81 3 3279 0771