

2 MP  
21.3"



# TOTOKU Color LCD Monitors CCL250i

Totoku's CCL250i is one of the brightest color, two megapixel displays in the market today. In addition to its extraordinary luminance, this display offers 100,000 hours of backlight life and a five year warranty.



## LCD

Technology	21.3-inch, Color, TFT active matrix
Display Area	432mm x 324mm
Pixel Pitch	0.270mm x 0.270mm

## Visual Performance

Contrast Ratio	450:1 (typ)
Max Luminance	450cd/m <sup>2</sup> (typ), (factory-set to 200cd/m <sup>2</sup> )
Viewing Angle	170° horizontal and vertical (typ)
Available Resolution	USTEXT, 640 x 480, 800 x 600, 1024 x 768, 1280 x 1024, 1600 x 1200
Color Display	Full color (16.77 million colors)

## Input

Signal Input	Sync Signal DVI 1.0 compliant
Plug and Play	DDC2B compliant

## Input

Power Supply	Input AC Adapter 100V-240V (±10%) 50/60Hz
Power Consumption	85W (max), (with power management feature)
Features	Calibration Control Luminance, Gamma, Color temp., Capability to save 3 sets of LUT settings (A calibration kit is required.)

OSD Information	Display Model name, Serial No., Total operating time, Calibration settings (Operating time since the last calibration, Luminance, Gamma, Color temp., etc.), Current luminance, etc.
-----------------	--

USB Hub	USB Rev. 2.0 compliant, 1USB upstream connector, 2 USB downstream connectors
Standards	UL60601-1, CSA C22.2 N601.1, MDD/CE, FDA 510(k), CCC, MIC, BSM, IFCC-B, VCCI-B,

## Physical Characteristics

Dimensions (WxHxD)	Landscape: 474mm x 468.4/529.9mm x 220mm, Portrait: 367mm x 521.9/583.4mm x 220mm
Weight Approx.	11.6kg (Approx. 7.4kg without tilt stand)
Tilt Stand	Tilt, swivel, landscape/portrait rotation
Mount	100mm VESA compliant
Security Slot	Antitheft security slot (Panel and tilt stand)
Protective Filter	Antireflection-coated protective filter
Accessories	AC adapter, 3P power cord, DVI cable, Serial cable, USB cable, User manual