

3 MP
20.8"



TOTOKU Color LCD Monitors CCL350i

Totoku's CCL350i includes the newest in backlight stabilization technology. With an integrated front sensor, the CCL350i eliminates backlight flicker, thereby reducing eye fatigue. It's high brightness and contrast make it an ideal solution for CR, MR and PET.



LCD

Technology	20.8-inch, Color, TFT active matrix
Display Area	423.9mm x 318.0mm
Pixel Pitch	0.207mm x 0.207mm

Visual Performance

Contrast Ratio	400:1 (typ)
Max Luminance	400cd/m ² (typ), (factory-set to 200cd/m ²)
Viewing Angle	170° horizontal and vertical (typ)
Available Resolution	USTEXT, 640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 2048 x 1536 (QXGA)
Color Display	Full color (16.77 million colors)

Input Signal

Input Sync Signal	DVI 1.0 compliant
Plug and Play	DDC2B compliant

Input Power Supply

Input	AC Adapter 100V-240V (±10%) 50/60Hz
Power Consumption	83W (max), (with power management feature)

Features

Calibration Control	Luminance, Gamma, Color temp., Capability to save 3 sets of LUT settings (A calibration kit is req.)
OSD Information	Display Model name, Serial No., Total operating time, Calibration settings (Operating time since the last calibration, Luminance, Gamma, Color temp., etc.), Current luminance, etc.
USB Hub	USB Rev. 2.0 compliant, 1 USB upstream connector, 2 USB downstream connectors
Standards	UL60601-1, CSA C22.2 N601.1, MDD/CE, FDA 510(k), CCC, MIC, BSMI, FCC-B, VCCI-B

Physical Characteristics

Dimensions (WxHxD)	Landscape: 474mm x 468.4/529.9mm x 220mm, Portrait: 367mm x 521.9/583.4mm x 220mm
Weight	Approx. 11kg (Approx. 6.8kg without tilt stand)
Tilt Stand	Tilt, swivel, landscape/portrait rotation
Mount	100mm VESA compliant
Security Slot	Antitheft security slot (Panel and tilt stand)
Accessories	AC adapter, 3P power cord, DVI cable, Serial cable, USB cable, User manual